



PRE-CUT TRUNKING SERIES P / FLEXIBLE SLOTTED TRUNKINGS SERIES 234

MAIN TECHNICAL FEATURES OF THE PRE-CUT TRUNKING:

- Made of: technopolymer on rigid PVC base, self-extinguishing V0 (UL94).
- Alternating holes for conduit diameters 18 mm and 23 mm.
- Perforated bottom for a quick installation, standard bar length: 2m.

MAIN TECHNICAL FEATURES OF THE FLEXIBLE SLOTTED TRUNKING:

- Made of: technopolymer on rigid PP base, self-extinguishing V2 (UL94).
- Perforated bottom for screw fixing or with adhesive tape.
- **Slots 7,5/5/7,5** - Standard length: 500 mm.



GREY RAL 7030

Pre-cut trunking for conduits Series P

ITEM	EXTERNAL DIMENSIONS W x H mm	PACKAGING m
ECP5050	Trunking and cover 50x50	24
ECP7550	Trunking and cover 75x50	40

Flexible slotted trunkings Series 234

ITEM		EXTERNAL DIMENSIONS W x H mm	PACKAGING PIECES
SCREW	ADHESIVE		
EC23401	EC23411	12,5x12,5x500	112
EC23402	EC23412	16x16x500	84
EC23403	EC23413	20x20x500	112
EC23404	EC23414	25x25x500	70
EC23405	EC23415	30x30x500	50
EC23406	EC23416	40x40x500	50
EC23407	EC23417	50x50x500	32

PRECUTTING OF THE TRUNKINGS P5050-P7550

